



Coil Tubing Mud System



A three compartment crimp wall tank measuring 43'Lx8'Wx7'T including two side pump pockets mounted on a Heavy duty, twin axel Rock over trailer 52' 11" with 10' porch, DOT certified, non permit highway legal, total capacity 280BBL.

Equipment:

- A 6-4 Mud Cleaner mounted over a 126E Triflo Shale Shaker.
- A Mud mixing hopper with jet complete with bag tray.
- A mud lab sink.
- Three 7.5HP Tri-Flo Agitators with XP Motors.
- Three, 3x4-2500 series, 25HP Centrifugal Pumps, with XP Motors, two mounted in side pockets and one on porch.
- A 146E Scalping Shale shaker.
- 24" Mud Gas Separator with hydraulic lay down system and stiff leg to floor.
- Water supply pump, 7.5HP Centrifugal 2X3 Space saver pump.
- Mounting bracket pad on front porch to install High pressure choke and manifold.
- Pit Volume Totalizing system complete with remote display panels.
- A Low float pump control system in the front tank compartment.
- 3 Immersion heaters mounted in tank compartments, two 8000 & one 3000 watt.
- Two hydraulic rams mounted in front of tank, to raise front trailer for hook up to tractor.
- A hydraulic power pack to operate the rams and MGS layover system.
- All necessary plumbing, valves, manifolds are included to meet system requirements.
- All necessary hand rails, catwalks, grating and ladders, easily stacked, OSHA Compliant.
- A 3" hydraulic drive submersible pump and flanges hoses to well head, 20' long. Customer to provide hydraulic power to pump.

Electrical:

- A NEMA Explosion proof electrical system, OSHA Compliant, with central control panel
- 3 Explosion proof, telescoping flood lights setup for single man operation.

Paint:

- Standard Triflo three step paint system: sand blast, primer and Urethane finish coat.

Triflo International, Inc.
1000 FM 830, Willis, TX 77318
P.O. Box 2626, Conroe, TX 77305
E-Mail info@triflo.com
Web Site www.triflo.com
Phone Number (963) 856-8551
Fax Number (936) 856-5668



