



Description:

Light, compact and efficient is what the Triflo 146L-6 shaker was designed around. At peak operation this double deck shaker uses smaller motors and is capable of hitting over 7 G's as shown on the Vibration Analysis report. With this shaker you get better G forces but with less motor which means better separation with less power needed for operation. With two decks you have the option of running a Possum Belly and a Mud Cleaner simultaneously all within the same foot print.

Specifications:

Process Rate:	Dependent on screen mesh	Number of screens:	Top deck-2 Bottom deck- 3
Cut Point:	Dependent on screen mesh	Size of screens:	2' x 4'
Length:	6' - 4"	Sq. Ft. of screens:	40 sq. ft.
Width:	5' - 9"	Available mesh sizes:	3 - 400 Mesh
Height:	4' - 4"	Volts:	230/460 v
Weight:	1846 LBS.	Hertz:	50/60 hz
		Horse Power:	2 .30
			XP or Non-XP available

Components

- Vibrator motor 150-4
- 146L-6 Deck Weldment
- 146L-6 Motor Mount

Triflo International, Inc.
 1000 FM 830, Willis, TX 77318
 P.O. Box 2626, Conroe, TX 77305
 E-Mail: info@triflo.com

Web Site: www.triflo.com
 Phone Number: (936) 856-8551
 Fax Number: (936) 856-5668

