



ES 500



Additional Features:

- Two Ex. Proof telescopic halogen flood lights
- Collapsible, partial wrap around catwalk with OSHA approved, removable stairs and handrails
- Optional Auger Catch Tank

Specifications:			
Dimensions	System is built on 30'L x 8"W HD Skid Tank is 4'H x 7.75' W x 23' L 5505 gallon cap	Operator Station	Single Class 1, Div 1, Enclosure for 1 person operation.
Tank	Three compartment	Pumps	Three 4 x 5 - 2500 Series
Electrical Requirements	460v, 60 Hz, 3Ph, Ex. Proof Class 1, Div 1. Can be supplied with 380 v, 50Hz, 3Ph	Solid Separation Equipment	1 Triflo Elliptical Scalping Shaker, Model 148E. One Triflo 12-4 Desilter with Vacuum adjustment over a Triflo Model 146 Elliptical Shaker. 1 Triflo 30-2 Clay ejector with vacuum adjustment over a Triflo Model 146 Elliptical Shaker. (All Shakers have fast change, pre-tensioned screens.)
Thru put Capacity	500 gallons per minute, continuous.	Mud Guns	Three Triflo 2" Mud Guns

Triflo International, Inc.
 1000 FM 830, Willis, TX 77318
 E-Mail info@triflo.com
 Web Site www.triflo.com
 Phone Number (963) 856-8551
 Toll Free (888) 225-2440

