

Technical Specifications & Features for the Triflo ES 300

Dimensions: 19'L x 6'6"W x 13'4" H on a HEAVY DUTY SKID

Tank: Three compartment

Electrical Requirements: 460v, 60 Hz, 3Ph, Ex. Proof Class 1, Div 1. Can be supplied with 380 v, 50Hz, 3Ph

Thru put Capacity: 300 gallons per minute, continuous.

Operator Station: Single Class 1, Div 1, Enclosure for 1 person operation.

Pumps: Three 3x4 - 250 Series

Solid Separation Equipment: 1 Triflo Elliptical Scalping Shaker, Model 146E. One Triflo 8-4 Desilter with Vacuum adjustment over a Triflo Model 126 Elliptical Shaker. 1 Triflo 20-2 Clay sector c/w vacuum adjustment over a Triflo Model 126 Elliptical Shaker. (All Shakers have fast change, pre-tensioned screens.)

Mud Guns: Three Triflo 2" Mud Guns

Additional Features:

- Two Ex. Proof telescopic halogen flood lights
- Collapsible, partial wrap around catwalk with OSHA approved, removable stairs and handrails
- Optional Auger Catch Tank

Service After the Sale

The most important asset Triflo has to offer is our select team of design, manufacturing and service-oriented personnel.

The Triflo serviceman is a trained professional prepared to analyze and skillfully handle your needs. In addition, to classroom training, each new employee works with a seasoned field serviceman until he is comfortable with a variety of procedures. The concept of the craftsman and his apprentice is a reality at Triflo.



ES 300 & ES 500



1000 FM 830 Willis, TX 77318

Phone: (936) 856 - 8551

www.triflo.com

Email: info@triflo.com



Environmental Systems for All Industries ES 300 & ES 500



Please contact our Project Quoting & Sales group for more information:

Phone:
(936) 856-8551